



1. ELECTRICAL SPECIFICATIONS

Accuracy is calculated as $\pm [\% \text{ readings} + (\text{no. of digits} \times \text{resolution})]$ at $23^\circ\text{C} \pm 5^\circ\text{C}$, relative humidity $<80\%\text{RH}$

SAFETY TEST

DMM – DC Voltage

Range [V]	Resolution [V]	Accuracy
3 ÷ 1000	1	$\pm (1.0\% \text{rdg} + 2 \text{dgt})$

DMM – AC TRMS Voltage

Range [V]	Resolution [V]	Accuracy
3 ÷ 1000	1	$\pm (1.0\% \text{rdg} + 3 \text{dgt})$

Frequency range: 42.5Hz ÷ 69Hz ; Voltage zeroed for measured values $<3\text{V}$

Insulation Resistance ($\text{M}\Omega$) – DUAL Mode

Test voltage DC [V]	Range [$\text{M}\Omega$]	Resolution [$\text{M}\Omega$]	Accuracy (*)
250, 500, 1000	0.1 ÷ 0.99	0.01	$\pm (5\% \text{rdg} + 5 \text{dgt})$
	1.0 ÷ 19.9	0.1	
	20 ÷ 100	1	

(*) Accuracy indicated for $\text{VPN} \geq 240\text{V}$, $R_{\text{fault}} \geq 10\text{M}\Omega$. Accuracy of R_p and $R(+)$ not declared if $R(+)$ $\geq 0.2\text{M}\Omega$ and $R(-)$ $< 0.2\text{M}\Omega$

Accuracy of R_p and $R(-)$ not declared if $R(+)$ $< 0.2\text{M}\Omega$ and $R(-)$ $\geq 0.2\text{M}\Omega$

Open voltage $< 1.25 \times$ nominal test voltage
Short circuit current $< 15\text{mA}$ (peak) for each test voltage
Nominal measured current $> 1\text{mA}$ on $R = 1\text{k}\Omega \times V_{\text{nom}}$ (with VPN, VPE, VNE = 0)
Managed capacity per poles: $2\mu\text{F}$

Insulation Resistance ($\text{M}\Omega$) – TMR Mode

Test voltage DC [V]	Range [$\text{M}\Omega$]	Resolution [$\text{M}\Omega$]	Accuracy
250, 500, 1000	0.01 ÷ 9.99	0.01	$\pm (5.0\% \text{rdg} + 5 \text{dgt})$
	10.0 ÷ 99.9	0.1	

Open voltage $< 1.25 \times$ nominal test voltage
Short circuit current $< 15\text{mA}$ (peak) for each test voltage
Nominal measured current $> 1\text{mA}$ on $R = 1\text{k}\Omega \times V_{\text{nom}}$ (with VPN, VPE, VNE = 0)
Setting timer: $3\text{s} \div 999\text{s}$

Continuity of protection conductors (RPE)

Range [Ω]	Resolution [Ω]	Accuracy
0.00 ÷ 9.99	0.01	$\pm (2\% \text{rdg} + 2 \text{dgt})$
10.0 ÷ 99.9	0.1	
100 ÷ 1999	1	

Test current: $> 200\text{mA}$ DC up to 5Ω (included cables), Resolution 1mA , Accuracy $\pm (5.0\% \text{rdg} + 5 \text{dgt})$
Open voltage $4 < V_0 < 10\text{V}$

GFL (Ground Fault Locator) function

Test voltage DC [V]	Range [$\text{M}\Omega$]	Resolution [$\text{M}\Omega$]	Accuracy R_p (*)	Position accuracy
250, 500, 1000	0.1 ÷ 0.99	0.01	$\pm (5\% \text{rdg} + 5 \text{dgt})$	$\pm 1 \text{module}$ ($\text{NMOD} \leq 35$) $\pm 3 \text{module}$ ($\text{NMOD} > 35$)
	1.0 ÷ 19.9	0.1		
	20 ÷ 100	1		

(*) Accuracy indicated for $\text{VPN} \geq 240\text{V}$, $R_{\text{fault}} \geq 10\text{M}\Omega$. Accuracy of R_p and $R(+)$ not declared if $R(+)$ $\geq 0.2\text{M}\Omega$ and $R(-)$ $< 0.2\text{M}\Omega$

Accuracy of R_p and $R(-)$ not declared if $R(+)$ $< 0.2\text{M}\Omega$ and $R(-)$ $\geq 0.2\text{M}\Omega$

Open voltage $< 1.25 \times$ nominal test voltage
Short circuit current $< 15\text{mA}$ (peak) for each test voltage
Nominal measured current $> 1\text{mA}$ on $R = 1\text{k}\Omega \times V_{\text{nom}}$ (with VPN, VPE, VNE = 0)
Managed capacity per poles: $2\mu\text{F}$
Set limit threshold on measure $0.05\text{M}\Omega$, $0.1\text{M}\Omega$, $0.23\text{M}\Omega$, $0.25\text{M}\Omega$, $0.50\text{M}\Omega$, $1.00\text{M}\Omega$
Number of set modules: $4 \div 60$

The GFL function allows obtaining correct results with the following conditions:

- Test carried out with $V_{\text{test}} \geq V_{\text{nom}}$ on a **single string** disconnected from the inverter, from possible arresters and from earth connections
- Test performed upstream of any blocking diodes
- **Single fault** of low insulation located at any position in the string
- Insulation resistance of the single fault: **$< 1.00\text{M}\Omega$**
- Environmental conditions similar to those in which the fault was reported

**OPT (Insulation test with optimizers and MLPE devices)**

Test voltage DC [V]	Range [MΩ]	Resolution [MΩ]	Accuracy Rp (*)
100, 250, 500, 1000 (MLPE with RSD)	0.1 ÷ 0.99	0.01	±(5%rdg + 10dgt)
	1.0 ÷ 19.9	0.1	
	20 ÷ 250	1	
100 (MLPE without RSD)	0.1 ÷ 0.99	0.01	
	1.0 ÷ 19.9	0.1	
	20 ÷ 100	1	

(*) Accuracy indicated for VPN ≥ 240V, R_{fault} ≥ 10Ω. Accuracy of Rp and R(+) not declared if R(+) ≥ 0.2MΩ and R(-) < 0.2MΩ

Accuracy of Rp and R(-) not declared if R(+) < 0.2MΩ and R(-) ≥ 0.2MΩ

Open voltage < 1.25 x nominal test voltage

Short circuit current < 15mA (peak) for each test voltage

Nominal measured current > 1mA on R = 1kΩ x V_{nom} (with VPN, VPE, VNE = 0)

Managed capacity per poles: 2μF

Set limit threshold on measure: 0.10MΩ, 0.25MΩ, 0.60MΩ, 1.00MΩ, 100MΩ, 200MΩ (MLPE with RSD)

0.10MΩ, 0.25MΩ, 0.60MΩ, 1.00MΩ, 50MΩ (MLPE without RSD)

Number optimizers: 1 ÷ 60

Max current in RSD mode: 1A (RSD = Rapid Shut Down function)

FUNCTIONALITY TEST (IVCK)**DC Voltage @ OPC**

Range [V]	Resolution [V]	Accuracy
3.0 ÷ 1000.0	0.1	±(1.0%rdg+2dgt)

Minimum VPN voltage to start the test: 15V

IDC Current @ OPC

Range [A]	Resolution [A]	Accuracy
0.10 ÷ 30.00	0.01	±(1.0%rdg+2dgt)

DC Voltage @ STC

Range [V]	Resolution [V]	Accuracy
3.0 ÷ 1000.0	0.1	±(4.0%rdg+2dgt)

IDC Current @ STC

Range [A]	Resolution [A]	Accuracy
0.10 ÷ 30.00	0.01	±(4.0%rdg+2dgt)

Irradiation with connection to HT305 reference cell

Voltage range [mV]	Resolution [mV]	Accuracy (*)
0.00 ÷ 99.99	0.01	±(1.0% rdg + 0.02mV)

Measurement range [W/m²]	Resolution [W/m²]	Accuracy (*)
0 ÷ 1400	1	±(1.0%rdg + 1dgt)

(*) Accuracy of instrument without cell

Module temperature with connection to PT305 probe

Resistance range [Ω]	Resolution [Ω]	Accuracy (*)
846 ÷ 1385	0.385	±(1.0%rdg + 3.85Ω)

Measurement range [°C]	Resolution [°C]	Accuracy (*)
-40.0 ÷ 99.9	0.1	±(1.0%rdg + 1°C)

(*) Accuracy of instrument without probe

2. GENERAL SPECIFICATIONS

DISPLAY AND MEMORY

Features:	240x240pxl custom LCD with backlight
Memory:	max 999 test, 3 marker levels
Internal database for PV modules:	max 64 saving modules

POWER SUPPLY

Internal power supply:	6x1.5V alkaline batteries type LR6, AA or 6x1.2V rechargeable NiMH batteries type LR6, AA (External adapter needed for NiMH batteries recharging)
Battery life (@Temp = 20°C):	RPE: >500 Test (RPE ≥ 0.1Ω) GFL, MΩ: >500 test (Riso ≥ 1kΩxVTest) IVCK: >500 test (no SOLAR03)
Auto Power OFF:	after 5 minutes of idleness

OUTPUT INTERFACE

PC communication port:	optical/USB and WiFi
Interface with SOLAR03:	Bluetooth BLE communication (up to 100m/328ft in free space)

MECHANICAL FEATURES

Dimensions (L x W x H):	235 x 165 x 75mm (9 x 6 x 3in)
Weight (batteries included):	1.2kg (25lv)
Mechanical protection:	IP40

ENVIRONMENTAL CONDITIONS

Reference temperature:	23°C ± 5°C (73°F ± 41°F)
Working temperature:	-10°C ÷ 50°C (14°F ± 122°F)
Working humidity:	<80%RH (without condensation)
Storage temperature:	-10°C ÷ 60°C (14°F ± 140°F)
Storage humidity:	<80%RH (without condensation)
Max height of use:	2000m (6562ft)

REFERENCE GUIDELINES

Safety:	IEC/EN61010-1, IEC/EN61010-2-030 IEC/EN61010-2-033, IEC/EN61010-2-034
EMC:	IEC/EN61326-1, IEC/EN61326-2-2
Safety of measurement accessories:	IEC/EN61010-031
IVCK measurements:	IEC/EN62446-1, IEC/EN60891, IEC/EN60904-1-5
MΩ measurement:	IEC/EN61557-2
RPE measurement:	IEC/EN61557-4
Insulation:	double insulation
Pollution degree:	2
Radio:	ETSI EN300328, ETSIEN301489-1, ETSIEN301489-17
Measurement category:	CAT III 1000V to ground Max 1000VAC, 1000VDC between inputs

This instrument complies with the requirements of the European Low Voltage Directives 2014/35/EU (LVD), EMC directive 2014/30/EU and RED 2014/53/EU directive
This instrument satisfies the requirements of 2011/65/EU (RoHS) directive and 2012/19/EU (WEEE) directive