



Puteri Disponibile:
650 VA

Tehnologia
Line Interactive



7

Motive pentru a alege Swap Client

- Tehnologia "LINE INTERACTIVE"
- Stabilizare cu Sistemul "AVR"
- Control Digital cu Microprocesor
- Gestione Avanzata della Batteria
- Forma de Unda Pseudo-SINUSOIDALA
- Functie "Cold-Start"
- Silentios

Conexiuni:

- 1 Priza de Alimentare
- 2 Prize de Iesire UPS
- 3 Fuzibili de Protectie

Sinoptic si Comenzi:

- 4 Buton On-Off
- 5 Indicare UPS Aprins
- 6 Indicare Carica Baterie
- 7 Indicare Alarne



Conexiuni

Panou Frontal

CARACTERISTICI TEHNICE**Generale**

Cod Articol:	SWC-650	SWC-850
Putere (VA):	650VA	850VA
Putere (W):	390W	510W
Tehnologia:	LINE-INTERACTIVE	LINE-INTERACTIVE

Intrare

Faze:	MONOFAZATE
Tensiune (Vac):	230Vac $\pm 25\%$
Frecventa (Hz):	50 - 60Hz $\pm 10\%$ (auto sensing)
Conexiune de Intrare:	IEC 60320 C14

Iesire

Faze:	MONOFAZATE
Tensiune (Vac):	230Vac
Reglare de Tensiune	5% in absenta de Reteaa, 10% in Prezenta de Reteaa
Frecventa (Hz):	50 - 60Hz $\pm 0,5\text{Hz}$ (in battery mode)
Forma de Unda:	PSEUDOSINUSOIDALA
Timp de Comutare:	2/7ms
Conexiune de Iesire:	n° 2 IEC 60320 C13

Baterie

Tensiune (Vdc):	12Vdc	12Vdc
Numar:	1	1
Tip:	Plumb ermetic fara intretinere	Plumb ermetic fara intretinere
Capacitate:	7Ah	7Ah
Timp de Incarcare (90%):	6-12 ore	6-12 ore
Autonomia Standard:	10 min.	10 min.
Protectie:	Impotriva descarcare excesiva, test bateria	

Protectii

La Suprasarcina:	110% per 60 sec. - 130% per 3sec.
La Scurt circuit:	Cu fuzibil
La Spike de Retea:	320 joules. 2 ms

Interfata

Semnalizari Optice:	Led frontali: stare UPS, incarcare baterie, anomalie/Alarne
Acustice:	Lipsa Reteaa; Baterie descarcate; Suprasarcina

Standarde

Securitate:	EN 62040-1-2
Conformitate EMC:	EN 62040-2
Surge Capability:	IEC 801-5

Note Generale

Temperatura Ambient:	0° -40° C	0° -40° C
Umiditate Relativa:	Pana la 90% (fara condens)	Pana la 90% (fara condens)
Zgomot:	0 dB	0 dB
Dimensiuni (LxPxH):	96x320x163mm	96x320x163mm
Greutate (Kg):	6Kg	7,5 Kg